



Sigma P5 Ultrasound



General Specifications

Dimensions & Weight

- Length: 390 mm (15.3 in)
- Width: 320 mm (12.6 in)
- Height: 70 mm (2.7 in)
- Weight: 6.35 kg (14 lbs)

Electrical Power

- Input Power: 100-240 V
- Input Current: <2 amps
- Lithium Ion 129 Wh Battery
- 3-hour Battery endurance

Operating Environment

- Ambient Temperature: - 20°C to 55°C (- 4°F ~ 131°F)
- Relative Humidity: 30% to 85% (no condensation)
- Atmospheric Pressure: 700 hPa to 1060 hPa

Console Design

- High-Resolution Display
- Control Panel
- Carry Handle
- Transducer Port & Locking Lever

System Configuration

- Sigma P5 Ultrasound System
- Probes
- Carrying Case Handle
- Battery
- ECG (*Optional)
- Needle-Guided Brackets (*Optional)

Inputs & Outputs

Main Unit

- Transducer Port
- I/O Extend Port
- Power Input Port/Power Adapter
- 2 USB3 Ports
- VGA Port
- Ethernet Port
- ECG Port
- S-Video: Separate Video Output
- Speakers

Mobile System Cart

- 3 Transducer Ports
- I/O Port
- Trolley Storage Tray
- Wireless-LAN Adapter

Peripheral Equipment

- Sony B/W Printer

User Interface

Display Screen

- 15" LCD, High-Res. (1024 x 768)

Control Panel

- Alphanumeric & Function Keys
- Navigation Rotary Knob
- 6 Segment TGC
- Power/Battery Indicator
- Trackball

System Overview

Applications

- Abdomen
- Small Parts
- ICU/CCU
- Interventional
- Obstetrics
- Gynecology
- Cardiology
- Peripheral Vessels
- Urology
- Anesthesia
- Emergency Medicine
- Pediatrics
- Neonate
- Trans-cranial
- Musculoskeletal
- Intra-operative

Imaging Modes

- B
- M
- CFM (Color)
- TVI (Tissue Velocity Imaging)
- PW
- CW

- TVD (Tissue Velocity Doppler)
- AMM (Anatomical M Mode)
- Real-Time Panoramic View
- Power Angio

Transducer Type

- Linear Array
- Convex Array
- Phased Array

Imaging Technology

Imaging Features

- Software-Defined Ultrasound (SDU)
- Floating Point All Digital Beamforming Technology
- Point-by-Point Dynamic Focus Beaming
- Adaptive Broadband Imaging
- OmniView Spatial Compounding
- Lossless Grayscale Conversion
- Tissue Harmonic Imaging
- Linear Steering
- Trapezoid Imaging
- Real-Time Panoramic View
- Adaptive Speckle Suppression
- Motion Adaptive Persistence
- Auto Optimization
- Wideband Harmonics (Pulse Inversion)
- Discreet Fourier Transform Spectrum Processing (DFT)

Intuitive Workflow

- Thumbnail Images: Display Images are Saved During Live Scanning
- Menus and Active Parameter Adjustments
- Reports: Edit & Preview Function
- Backlight Indication
- Hot-Plug for Transducer
- Auto Power Save
- Boot Time: 20 seconds

Imaging Display

- Zoom (8x Magnification)
- Split Screen

Distributed by:



774 S. Northlake Blvd,
Suite 1016, Altamonte
Springs, FL 32701
855-892-3872

www.carestreamamerica.com

Copyright ©2016 Whale Imaging, Inc. The Whale logo, P-Series, and Sigma P5 are Trademarks of Whale Imaging, Inc. or its affiliates and may not be copied or otherwise used without express written permission. All reasonable efforts are made to ensure the accuracy of content within this media material. Whale Imaging, Inc. will not be held responsible in whole or in part for any inaccuracies or omissions contained within. Sigma P5 is 510(k) approved for the USA and CE approval is pending for the European Union. Docref: WIU/LH/080416-1.